FLEXICLEAN TOOL

Description

FlexiClean is an ROV-deployed cleaning tool for removing marine growth and debris on underwater structures and equipment. It has proved extremely effective on sensitive surfaces such as flexible risers with its ability to clean without damaging the riser's outer sheath. The tool's unique design provides lengthy operation with no loss of performance from clogged cleaning elements, and its tough, flexible elastomeric material resists entanglement.

Specifications

- Hydraulic Requirements: 2000 psi (138 Bar), 4-16 gpm (15-60 lpm)
- Depth Rating: 10,000 ft (3000 m)
- Deployment: Manipulator
- Weight In Air: 35 lb (15.9 kg)
- Weight In Sea Water: 18 lb (8.2 kg)
- Dimensions:
  22.5 (W) x 22.5 (L) x 21.25 (H)
  572mm (W) x 572mm (L) x 540mm (H)
- Applications:
  Mooring chains and wires
  Risers
  Vessel hulls
  Subsea Structures

TIDEWATER® SUBSEA

Corporate: 6002 Rogerdale Rd, Suite 600 • Houston, TX • 77072 • USA
Operations: 5661 Brittmoore Rd • Houston, TX • 77072 • USA
P: +1 713.470.5500 • F: +1 713 470 0077
www.tdw.com

NOTE: Specifications subject to change without notice. For further information, contact Tidewater Subsea, L.L.C.

Doc No. 0000-BD-SPC-05021 Rev 03