



LOUSTEAU TIDE as shown  
BOURGEOIS TIDE similar

Vessel Characteristics

Length, Overall:	207 ft	63.1 m
Beam:	53 ft	16.2 m
Depth:	19 ft	5.8 m
Maximum Draft:	16.2 ft	4.9 m
Light Draft:	8.6 ft	2.6 m
Minimum Height:	61.8 ft	18.8 m
Freeboard:	2.8 ft	0.8 m
Displacement:	3,540 lt	3,590 mt
Deadweight:	1,970 lt	2,000 mt
Clear Deck Space:	107 x 44 ft	33 x 13 m
Clear Deck Area:	4,720 ft <sup>2</sup>	440 m <sup>2</sup>
Deck Strength:	1,020 lb/ft <sup>2</sup>	5 t/m <sup>2</sup>
Class Notations:	ABS: +A1, +AMS, +DPS-1	

# TIDEWATER<sup>®</sup>

## BOURGEOIS TIDE

**BOLLINGER 207' PLATFORM SUPPLY VESSEL**

# TIDEWATER<sup>®</sup> BOURGEOIS TIDE

Capacities			
Deck Cargo:	1,210 lt		1,230 t
Fuel Oil:	109,000 gal		410 m <sup>3</sup>
Potable Water:	82,400 gal		310 m <sup>3</sup>
Fresh Water:	138,000 gal		520 m <sup>3</sup>
Drill/Ballast Water:	26,200 gal		99.1 m <sup>3</sup>
Bulk Tanks (5 tanks):	6,000 ft <sup>3</sup>		170 m <sup>3</sup>
Liquid Mud (22 lbs/gal):	6,240 bbl		990 m <sup>3</sup>

Machinery			
Main Engines (2):	CAT 3516B HD DITA		
Total HP:	4,750		
Z-Drives:	Yes		
Propellers (2):	Rolls Royce US 205 1771KW FPP		
Kort Nozzles:	2		
Primary Generators (3):	190 kw	480 v	60 hz
Driven by:	CAT 3306		
Emergency Generators (1):	100 kw	480 v	60 hz
Driven by:	CAT 3304		
Bow Thruster (1):	Azimuthing Swing-Down/Tunnel		
Driven by:	CAT 3508 B 1050 HP		
Total Thrust:	13.1 st		11.9 mt

Deck Equip.	
Anchors (2):	4230 lbs Navy Stockless
Anchor Chain:	270 m of 38 mm chain per side
Tugger (1):	10 t COASTAL MARINE, HYDRAULIC

Accommodations	
Nº of Berths:	21
1-man cabins:	3
2-man cabins:	5
4-man cabins:	2
Certified to Carry:	21

Performance		
(Approximate values assuming Ideal Conditions)		
<i>Fuel Consumption Vs Speed</i>		
Maximum:	16.6 m <sup>3</sup> /day (180 gph) @ 12 knots	
Cruising:	12.4 m <sup>3</sup> /day (140 gph) @ 10 knots	
Economical:	10 m <sup>3</sup> /day (110 gph) @ 8 knots	
Standby:	1.4 m <sup>3</sup> /day (15.4 gph) @ 0 knots	
Range @ 10 Knots:	7,830 nm	
<i>Transfer Rates</i>		
Fuel Oil:	500 gpm @ 350 ft	110 m <sup>3</sup> /h @ 100 m
Drill/Ballast Water:	600 gpm @ 250 ft	140 m <sup>3</sup> /h @ 77 m
Bulk:	20 cfm @ 230 ft	34 m <sup>3</sup> /h @ 70 m
Liquid Mud:	800 gpm @ 150 ft	180 m <sup>3</sup> /h @ 47 m

Nav/Comms Equip.	
Radar(s):	2
Depth Sounder:	1
Gyro Compass:	2
Doppler Log:	1
Radio:	3 x VHF; 1 x SSB

Special Equip.	
Firefighting:	FiFi-1 Unclassed
Dynamic Positioning:	DP-1 CLASSED
Ref. Systems:	1 x MRU; 2 x DGPS 1 x Laser-based
Mud Recirculation:	Yes
Tank Cleaning:	Yes
Rescue Boat:	FRC - 15 Persons

Registration		
Flag:	VANUATU	
IMO Nº:	9273466	
Year Built:	2004	
Builder:	BOLLINGER	
Call Sign:	YJSY2	
Tonnage (ITC):	1624 GT	511 NT

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein. Fuel consumption figures are historically conservative approximations.