MALONGO TIDE





ALUCAT 1905 FAST CREWBOAT

Vessel Characteristics

Length, Overall:	69.2 ft	21.1 m
Beam:	18.7 ft	5.7 m
Depth:	8.2 ft	2.5 m
Maximum Draft:	4.6 ft	1.4 m
Minimum Height:	28.9 ft	8.8 m
Freeboard:	3.6 ft	1.1 m
Displacement:	50 lt	50 mt
Deadweight:	10 lt	10 mt
Clear Deck Space:	21 x 14 ft	6.4 x 4.2 m
Clear Deck Area:	150 ft²	14 m ²
Deck Strength:	200 lb/ft²	1 t/m²
Class Notations:	BUREAU VERITAS: 1+Hul 3	l, Mach, Crew boat,SEA AREA

Capacities

Deck Cargo:	2.2 lt	2.2 t
Fuel Oil:	1,630 gal	6.2 m ³
Potable Water:	64 gal	0.2 m ³



tdw.com

Pg.2 Further Specifications Pg.3 General Arrangement

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatspever arising out of the use or inability to use the data contained herein.

MALONGO TIDE Further specifications



Machinery

Main Engines (2):	CAT C32 ACERT		
Total HP:	2,600		
Propellers (2):	Waterjets Hamilton HM 521		
Primary Generators (1):	27 kw	380 v	60 hz
Driven by:		Cat	erpillar C2.2 T

Performance*

Fuel Consumption Vs Speed	
Maximum:	11.7 m³/day (130 gph) @ 32 knots
Cruising:	9.1 m³/day (100 gph) @ 21 knots
Economical:	7 m³/day (76.9 gph) @ 15 knots
Standby:	0.2 m³/day (2.5 gph) @ 0 knots
Range @ 21 Knots:	340 nm

Nav/Comms Equipment

Radar(s):	2
Depth Sounder:	1
Radio:	2 x VHF; 1 x SSB

Accommodations

Passenger Seats:	34
Certified to Carry:	36

Special Equipment

Firefighting:	FiFi Other	1x 300 Fire Monitor
---------------	------------	---------------------

Registration

Flag: VANUATU	F	Iome Port: PORT VILA
Hull Number:		2304
Year Built: 2013		Call Sign: YJTE9
Builder:		DAMEN
Tonnage (ITC):	59 GT	17 NT

Deck Equipment

Anchors (1):	FORTRESS FX-85 46.7 LBS
Anchor Chain:	10.1 m of 12.7 mm chain per side

*Approximate values assuming Ideal Conditions

tdw.com

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.


MALONGO TIDE


General Arrangement (Current configuration may vary.)





Profile





Below maindeck

tdw.com

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due dilige to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.