NAMIBE TIDE





ALUCAT 1905 FAST CREWBOAT

Vessel Characteristics

Length, Overall:	69.2 ft	21.1 m
Beam:	18.7 ft	5.7 m
Depth:	8.2 ft	2.5 m
Maximum Draft:	4.6 ft	1.4 m
Minimum Height:	28.9 ft	8.8 m
Freeboard:	3.6 ft	1.1 m
Displacement:	50 lt	50 mt
Deadweight:	10 lt	10 mt
Clear Deck Space:	21 x 14 ft	6.4 x 4.2 m
Clear Deck Area:	150 ft ²	14 m ²
Deck Strength:	200 lb/ft²	1 t/m²
Class Notations:	BUREAU VERITAS: 1+Hull, Mach, Crew boat,SEA AREA	

Capacities

Deck Cargo:	2.2 lt	2.2 t
Fuel Oil:	1,630 gal	6.2 m ³
Potable Water:	64 gal	0.2 m ³

TIDEWATER

Find out more

tdw.com

Pg.2 Further Specifications Pg.3 General Arrangement

NAMIBE TIDE

Further specifications



Machinery

Main Engines (2):		CA	AT C32 ACERT
Total HP:			2,600
Propellers (2):		Waterjets Ha	milton HM521
Primary Generators (1):	27 kw	380 v	60 hz
Driven by:		Cat	erpillar C2.2 T

Performance*

Fuel Consumption Vs Speed	
Maximum:	11.7 m³/day (130 gph) @ 32 knots
Cruising:	9.1 m³/day (100 gph) @ 21 knots
Economical:	7 m³/day (76.9 gph) @ 15 knots
Standby:	0.2 m³/day (2.5 gph) @ 0 knots
Range @ 21 Knots:	340 nm

Deck Equipment

Anchors (1):	FORTRESS FX-85 46.7 LBS
Anchor Chain:	10.1 m of 12.7 mm chain per side

Nav/Comms Equipment

Radar(s):	2
Depth Sounder:	1
Radio:	2 x VHF; 1 x SSB

Accommodations

Passenger Seats:	34
Certified to Carry:	36

Special Equipment

Firefighting:	FiFi Other	1x 300 Fire Monitor
---------------	------------	---------------------


Registration


Flag: VANUATU	Home Port: PORT VILA	
Hull Number:	2302	
Year Built: 2013	Call Sign: YJTD5	
Builder:	DAMEN SHIPYARDS	
Tonnage (ITC):	59 GT 17 NT	


NAMIBE TIDE

General Arrangement (Current configuration may vary.)









Below maindeck