

# PACIFIC VALHALLA



PACIFIC VIXEN as shown, PACIFIC VALHALLA similar

## IMT 966 AHTS

### Vessel Characteristics

Length, Overall:	216.5 ft	66 m
Beam:	52.5 ft	16 m
Depth:	24 ft	7.3 m
Maximum Draft:	20.3 ft	6.2 m
Freeboard:	3.6 ft	1.1 m
Displacement:	4,530 lt	4,600 mt
Deadweight:	2,450 lt	2,480 mt
Clear Deck Space:	107 x 42 ft	33 x 13 m
Clear Deck Area:	4,480 ft <sup>2</sup>	420 m <sup>2</sup>
Deck Strength AFT:	1,020 lb/ft <sup>2</sup>	5 t/m <sup>2</sup>
Class Notations:	DNV: +1A, Fire fighter(I), Offshore service vessel(Anchor handling, Towing), DYNPOS(AUTR), EO	

### Capacities

Deck Cargo:	860 lt	870 t
Fuel Oil:	299,000 gal	1,130 m <sup>3</sup>
Potable Water:	120,000 gal	460 m <sup>3</sup>
Drill/Ballast Water:	246,000 gal	930 m <sup>3</sup>
Bulk Tanks (4 tanks):	6,530 ft <sup>3</sup>	180 m <sup>3</sup>
Liquid Mud (2.5 SG*):	2,920 bbl	460 m <sup>3</sup>
*Max Structural Specific Gravity		
Brine:	780 bbl	120 m <sup>3</sup>
Oil Dispersant:	2,550 gal	9.6 m <sup>3</sup>

## TIDEWATER

Find out more

[tdw.com](https://tdw.com)

Pg.2 Further Specifications  
Pg.4 General Arrangement

Pg.5 Capacity Table  
Pg.6 DP Capability Plot

**NOTICE:** The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

LAST UPDATE: 11/19/2023

# PACIFIC VALHALLA

## Further specifications



### Machinery

Main Engines (2):	MAN 9L27/38		
Total HP:	8,810		
Propellers (2):	MAN CPP		
Gears (2):	MAN		
Kort Nozzles:	2		
Rudders (2):	HI-LIFT FLAP RUDDERS		
Primary Generators (1):	270 kw	440 v	60 hz
Driven by:	CAT 3406		
Secondary Generators (2):	1,280 kw	440 v	60 hz
Driven by:	MAIN ENGINES		
Emergency Generators (1):	270 kw	440 v	60 hz
Driven by:	CAT 3406		
Bow Thruster (2):	BRUNVOLL FU-63-LTC-1550		
Driven by:	600KW ELECTRIC MOTORS		
Total Thrust:	20.1 st	18.2 mt	
Stern Thruster (2):	BRUNVOLL FU-63-LTC-1550		
Driven by:	600KW ELECTRIC MOTORS		
Total Thrust:	20.1 st	18.2 mt	

### Performance\*

<b>Fuel Consumption Vs Speed</b>		
<i>Maximum:</i>	271 m³/day (300 gph) @ 13 knots	
<i>Cruising:</i>	20.7 m³/day (230 gph) @ 11 knots	
<i>Economical:</i>	15 m³/day (170 gph) @ 10 knots	
<i>Standby:</i>	1.3 m³/day (14.3 gph) @ 0 knots	
<b>Bollard Pull</b>	140 st	120 mt
<b>Transfer Rates</b>		
<i>Fuel Oil:</i>	440 gpm @ 230 ft	100 m³/h @ 71 m
<i>Potable Water:</i>	660 gpm @ 230 ft	150 m³/h @ 71 m
<i>Drill/Ballast Water:</i>	660 gpm @ 230 ft	150 m³/h @ 71 m
<i>Bulk:</i>	27.3 cfm @ 190 ft	46.3 m³/h @ 57 m
<i>Liquid Mud:</i>	330 gpm @ 600 ft	75 m³/h @ 180 m
<i>Brine:</i>	330 gpm @ 600 ft	75 m³/h @ 180 m

### Tow/Anchor Handling

<b>Winch:</b>	Double Drum Winch (320T Brake)
<i>Model:</i>	Hydrakraft/Odim 250T Waterfall
<i>Line Pull:</i>	250 mt
<i>Tow/AH Wire:</i>	1,500 m / 1,500 m of 71 mm
<b>Pennant Reels (2):</b>	1,500 m of 71 mm
<b>Shark Jaw:</b>	2 X 300 T SWL
<b>Tow Pins:</b>	2 X 160 T SWL
<b>Chain Lockers (1):</b>	2,400 m of 76mm chain
<b>Chain Handler:</b>	1X76MM + 1X84MM
<b>Stern Roller:</b>	RRM SINGLE DRUM (2 X 5.5 M); 400 mt SWL
<b>Misc. Tow Equipment:</b>	1xSpare Store Reel 1000m x 76mm; 1x200 t Smit Towing Bracket

### Nav/Comms Equipment

<b>Radar(s):</b>	2
<b>Depth Sounder:</b>	1
<b>Gyro Compass:</b>	3
<b>Wind Seed Indicators:</b>	3
<b>Doppler Log:</b>	1
<b>Radio:</b>	2 x VHF; 1 x SSB
<b>Sat Com:</b>	2 X INMARSAT C

### Accommodations

<b>No. of Berths:</b>	30
<b>Cabins:</b>	8x1-man, 3x2-man & 4x4-man
<b>Certified to Carry:</b>	30
<b>Galley seating:</b>	14
<b>Hospital:</b>	Yes

### Deck Equipment

<b>Anchors (2):</b>	2100 KG
<b>Anchor Chain:</b>	440 m of 36 mm chain per side
<b>Windlass:</b>	10T Hydrakraft
<b>Crane (1):</b>	5 t @ 13 m
<b>Capstans (2):</b>	10 t HYDRAKRAFT
<b>Tugger (2):</b>	10 t HYDRAKRAFT

\*Approximate values assuming Ideal Conditions

tdw.com

**NOTICE:** The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

LAST UPDATE: 11/19/2023




## Registration

Flag: SINGAPORE	Home Port: SINGAPORE	
Hull Number: 162	IMO N <sup>o</sup> : 9361641	
Year Built: 2007	Call Sign: 9V6790	
Builder:	P.T. Nanindah Mutiara Shipyard	
Tonnage (ITC):	2147 GT	644 NT

## Special Equipment

Fire Fighting:	FiFi-1
Dynamic Positioning:	DP-2
Ref. Systems:	2 x MRU; 2 x DGPS 1 x Laser-based
Mud Circulation System:	Yes
Rescue Zone:	Yes
Rescue Boat:	Maritime Partner MP660 Springer, 10 Persons
Reefer Sockets:	6x 440V 63A; 2x220V
Misc:	MSD; HiPAP Ready; ROV Sockets: 2x440V 500A 3ph, 1x440V 63A0V 3ph, 1x440V 32A 3ph


\*Approximate values assuming Ideal Conditions







\*Capacities shown are for lead vessel. Actual capacities may vary slightly.  
 \*Capacities shown in **RED** are excluded from the total volume.  
 \*Capacities shown in **BLUE** are included in another Tank's Capacity.  
 \*Capacities shown in **GREEN** are counted for multiple Tank Capacities.



Wind Angle is stepped from 0 to 360 deg.  
Wave Angle is stepped from 0 to 360 deg.  
Current Angle is stepped from 0 to 360 deg.

Wind Speed is Set Automatically.  
Wave Height is Derived from Wind Speed.  
Current Speed is 1.5 knots.

