SEEKER TIDE

SEARCHER TIDE as shown, SEEKER TIDE similar

UT 751 E PSV

Vessel Characteristics

Length, Overall:	308.1 ft	93.9 m
Beam:	68.9 ft	21 m
Depth:	26.9 ft	8.2 m
Maximum Draft:	21.7 ft	6.6 m
Light Draft:	11.1 ft	3.4 m
Minimum Height:	99.4 ft	30.3 m
Freeboard:	5.3 ft	1.6 m
Displacement:	8,440 lt	8,580 mt
Deadweight:	4,800 lt	4,880 mt
Clear Deck Space:	201 x 58 ft	61 x 18 m
Clear Deck Area:	11,500 ft^2	1,070 m^2
Deck Strength AFT:	2,050 lb/ft^2	10 t/m^2
Class Notations:	DNV: +1A1, Fire fighter(I), Supply vessel, Clean, COM-F(V-3), DK(+), DYNPOS(AUTR), E0, HL(2.8), Ice(C), LFL(*), NAUT(OSV(A)), OILREC, SF	

Capacities

Deck Cargo:	3,070 lt	3,120 t
Fuel Oil:	348,000 gal	1,320 m^3
Potable Water:	83,300 gal	320 m^3
Fresh Water:	178,000 gal	670 m^3
Drill/Ballast Water:	385,000 gal	1,460 m^3
Bulk Tanks (7 tanks):	10,900 ft^3	310 m^3
Liquid Mud (2.8 SG*): *Max Structural Specific Gravity	5,730 bbl	910 m^3
Methanol:	1,300 bbl	210 m^3
Base Oil:	1,510 bbl	240 m^3
Brine:	2,540 bbl	400 m^3
Fire Fighting Foam:	530 gal	2 m^3

TIDEWATER

Find out more **tdw.com**

Pg.2 Further Specifications
Pg.3 General Arrangement
Pg.4 Capacity Table
Pg.5 DP Capability Plot

LAST UPDATE: 10/1/2026

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

SEEKER TIDE

Further specifications

Machinery

Diesel Electric Vessel			
Propulsive/Total HP:			5,900 / 9,470
Z-Drives:			Yes
Propellers (2):			AQUAMASTER AZP120, 2200KW CPP
Primary Generators (4):	1,660 kw	690 v	60 hz
Driven by:			RRM C25:33L6A
Emergency Generators (1):	150 kw	690 v	60 hz
Driven by:			SCANIA DI 12 62M
Bow Thruster (3):			2x RR TT2400 DPN TT FP, 1x RR TCNS 73/50
Driven by:			895KW ELECTRIC MOTORS
Total Thrust:		45 st	40.8 mt

Deck Equipment

Anchors (2):	4320 KG SPEK
Anchor Chain:	270 m of 50 mm chain per side
Windlass:	2x 20 MT RRM
Crane (2):	10 t @ 10 m
Tugger (1):	15 t RRM

Accommodations

No. of Berths:	25
Cabins:	13x1-man & 6x2-man
Certified to Carry:	25
Galley seating:	14
Hospital:	Yes

Registration

Flag: ISLE OF MAN		**Home Port:** DOUGLAS
Hull Number: 47		**IMO N°:** 9381691
Year Built: 2008		**Call Sign:** MSPN4
Builder:		Brevik Construction AS
Tonnage (ITC):	4755 GT	1760 NT

Performance*

Fuel Consumption Vs Speed		
Maximum:		27 m³/day (300 gph) @ 16.5 knots
Cruising:		17 m³/day (190 gph) @ 12.2 knots
Economical:		14.5 m³/day (160 gph) @ 11.3 knots
Standby:		2.9 m³/day (31.9 gph) @ 0 knots
Range @ 12.2 Knots:		22,500 nm
Transfer Rates		
Fuel Oil:	1100 gpm @ 300 ft	250 m³/h @ 92 m
Fresh Water:	1100 gpm @ 300 ft	250 m³/h @ 92 m
Drill/Ballast Water:	1100 gpm @ 300 ft	250 m³/h @ 92 m
Bulk:	26 cfm @ 190 ft	44.1 m³/h @ 57 m
Liquid Mud:	550 gpm @ 800 ft	120 m³/h @ 240 m
Base Oil:	660 gpm @ 300 ft	150 m³/h @ 92 m
Brine:	440 gpm @ 800 ft	100 m³/h @ 240 m
Methanol:	440 gpm @ 300 ft	100 m³/h @ 92 m

Nav/Comms Equipment

Radar(s):	2
Depth Sounder:	1
Gyro Compass:	3
Wind Speed Indicators:	2
Doppler Log:	1
Radio:	3 x VHF; 1 x SSB
Sat Com:	2X INMARSAT-C

Special Equipment

Firefighting:	FiFi-1
Dynamic Positioning:	DP-2
Ref. Systems:	2 x MRU; 2 x DGPS 1 x Microwave-based; 1 x Laser-based
Mud Circulation System/ Mud Mixers:	Yes/Yes
Tank Cleaning:	Yes
Rescue Zone:	Yes
Rescue Boat:	2x 10-Man Springer MP 800 FRC
Misc:	ORO Capacity - 1113.4 m3; MSD - 25 Persons; HPR Room; Eye Wash Station; Winching Zone; Dacon Scoop SB

*Approximate values assuming Ideal Conditions

tdw.com

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

LAST UPDATE: 10/1/2026

SEEKER TIDE

General Arrangement (Current configuration may vary.)



C–DECK



B–DECK



A–DECK



PLAN B



PLAN A



MAIN DECK



WHEELHOUSE TOP





BRIDGE DECK





D–DECK



PROFILE

tdw.com

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

LAST UPDATE: 10/1/2026

SEEKER TIDE

Capacity Table

Tank	Contents	Volume m^3	Base Oil	Fuel Oil	Dry Bulk	DW/WB	Potable Water	Fresh Water	Brine	Liquid Mud	Methanol	Lube Oil	Foam	Oil Disp.
FOREPEAK TK	DW/WB	163.7				163.7								
FO DB TK 7 C	DW/WB	63.1				63.1								
AFT PEAK TK SB	DW/WB	107.8				107.8								
AFT PEAK TK PS	DW/WB	107.8				107.8								
ROLL RED. TK 1	DW/WB	349.9				349.9								
ROLL RED. TK 2	DW/WB	310.2				310.2								
ROLL RED. TK 3	DW/WB	354.2				354.2								
FW DB/WG TK 1 SB	Ship's FW	157.7					157.7							
FW DB/WG TK 1 PS	Ship's FW	157.7					157.7							
FW DB/WG TK 2 SB	FW	115.8						115.8						
FW DB/WG TK 2 PS	FW	117.2						117.2						
FW DB/WG TK 7 SB	FW	82.8						82.8						
FW DB/WG TK 7 PS	FW	82.8						82.8						
FW WG TK 8 SB	FW	137.6						137.6						
FW WG TK 8 PS	FW	137.6						137.6						
FO DB/WG TK 3 SB	FO	150.6		150.6										
FO DB/WG TK 3 PS	FO	154.4		154.4										
FO DB/WG TK 4 SB	FO	211.1		211.1										
FO DB/WG TK 4 PS	FO	218.8		218.8										
FO DB/WG TK 5 SB	FO	238.0		238.0										
FO DB/WG TK 5 PS	FO	275.0		275.0										
FO DB TK 6 C	FO	70.7		70.7										
FO SERV TK SB	FO	36.9		36.9										
FO SERV TK PS	FO	36.9		36.9										
FO SETTL TK SB	FO	38.3		38.3										
FO DRAIN TK	FO	18.3		18.3										
FO OVERFLOW	FO	39.3		39.3										
BO TK 4 C	BO	118.3	118.3											
BO TK 5 C	BO	121.6	121.6											
METH TK 1 SB	METH	103.3									103.3			
METH TK 1 PS	METH	103.3									103.3			
CIRCULAR TK 1 C	LM/ORO	165.3								165.3				
CIRCULAR TK 2 C	LM/RS/ORO	165.3								165.3				
CIRCULAR TK 1 SB	BRI	101.1							101.1					
CIRCULAR TK 1 PS	BRI	101.1							101.1					
CIRCULAR TK 2 SB	BRI/ORO	101.1							101.1					
CIRCULAR TK 2 PS	BRI/ORO	101.1							101.1					
CIRCULAR TK 3 SB	LM/ORO	145.1								145.1				
CIRCULAR TK 3 PS	LM/ORO	145.1								145.1				
CIRCULAR TK 4 SB	LM/ORO	145.1								145.1				
CIRCULAR TK 4 PS	LM/ORO	145.1								145.1				
DRY BULK 1	DRY BULK	44.1			44.1									
DRY BULK 2	DRY BULK	44.1			44.1									
DRY BULK 3	DRY BULK	44.1			44.1									
DRY BULK 4	DRY BULK	44.1			44.1									
DRY BULK 5	DRY BULK	44.1			44.1									
DRY BULK 6	DRY BULK	44.1			44.1									
DRY BULK 7	DRY BULK	44.1			44.1									
LO TK 1 PS	LO	3.5										3.5		
LO TK 2 PS	LO	7.0										7.0		
LO TK 3 PS	LO	3.5										3.5		
LO TK 4 PS	LO	13.0										13.0		
LO TK 5 PS	LO	3.5										3.5		
LO TK 6 PS	LO	7.0										7.0		
FOAM TANK	FOAM	2.0											2.0	
Total Volume [m^3]			240.0	1,488.1	308.6	1,456.6	315.3	673.8	404.5	911.2	206.5	37.7	2.0	0.0
Spec Sheet Total Volume [m^3]			240.0	1,318.5	308.6	1,456.6	315.3	673.8	404.5	911.2	206.5	37.7	2.0	0.0

***Capacities shown are for lead vessel. Actual capacities may vary slightly.**

***Capacities shown in RED are excluded from the total volume.**

***Capacities shown in BLUE are included in another Tank's Capacity.**

***Capacities shown in GREEN are counted for multiple Tank Capacities.**

LAST UPDATE: 10/1/2026

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

SEEKER TIDE

DP Capability Plot



External:
Variable wind velocity rotating 360 deg
0.51 m/s wind generated current rotating 360 deg (0.0 deg offset)
Variable wave height rotating 360 deg (0.0 deg offset)

NOTICE: The data contained herein is provided for convenience of reference to allow users to determine the suitability of the Company's equipment. The data may vary from the current condition of equipment which can only be determined by physical inspection. Company has exercised due diligence to insure that the data contained herein is reasonably accurate. However, Company does not warrant the accuracy or completeness of the data. In no event shall Company be liable for any damages whatsoever arising out of the use or inability to use the data contained herein.

LAST UPDATE: 10/1/2026