



PSV

Serenade Tide

Vessel specs

Built	2009
Design	UT 751 CD
Yard	STX Brevik
Flag	NOR
LOA	93.9m
Breadth Moulded	21m
Deck Dimensions	1002,14m ² (56,3m x 17,8m)
Deck Load	3300mt
Main Class	+1A1, SF, E0, DK(+), HL(2,8), SUPPLY VESSEL BASIC, LFL*, COMF-V(3), CLEAN DESIGN, OILREC, DYNPOS-AUTR, NAUT OSV(A), ICE-C
Classification Society	DNV GL
Dynamic Positioning	DP 2 from Rolls Royce
Draft (max)	7.27m + 0m Skeg/Nozzle
Deadweight	5944mt (d=7.27m)
Deck Strength	10mt/m ²
Consumption at Service Speed	17m ³ / 24hrs @ 12,2Knots
Consumption at Economy Speed	14,5m ³ / 24hrs @ 11,3Knots
Base Oil	276m ³ / 1736bbbls
Brine	388m ³ / 2441bbbls
Drill Water / WB	2522m ³ / 15863bbbls
Dry Bulk	201,3m ³ / 7108cuft (4 tanks)
Fuel Oil	1260m ³ / 7925bbbls
Methanol	218m ³ / 1371bbbls
Slop	589m ³ / 3705bbbls
Mud	1137m ³ / 7152bbbls
Pot Water	1158m ³ / 7284bbbls
Accommodation	25 Persons
Cabins	13 x 1 Person, 6 x 2 Persons