



PSV

Spark Tide

Vessel specs

Built	2013
Design	PX 105
Yard	Zhejijang Shipbuilding
Flag	Marshall Islands
LOA	89m
Breadth Moulded	19m
Deck Dimensions	1010,4m ² (63,15m x 16,0m)
Deck Load	2537mt
Main Class	+1A1, SF, E0, DK(+), HL(2,8), OFFSHORE SERVICE VESSEL, COMF-V(3), CLEAN DESIGN, DYNPOS-AUTR, ICE-C, Fire Fighting Ship 1
Classification Society	DNV GL
Dynamic Positioning	DP 2 from Kongsberg
Draft (max)	6,65m + 0m Skeg/Nozzle
Deadweight	4459mt (d=6,60m)
Deck Strength	10 t/m ² aft fr. 49. fwd fr. 49: 5mt/m ²
Consumption at Service Speed	16m ³ / 24hrs @ 12Knots
Consumption at Economy Speed	10m ³ / 24hrs @ 10Knots
Base Oil	225m ³ / 1415bbbls
Brine	369m ³ / 2321bbbls
Drill Water / WB	2191m ³ / 13781bbbls
Dry Bulk	320m ³ / 11299cuft (5 tanks)
Fuel Oil	1076m ³ / 6768bbbls
Methanol	146m ³ / 918bbbls
Mud	870m ³ / 5472bbbls
Pot Water	726,5m ³ / 4570bbbls
Total Capacity	26 Persons
Cabins	14 x 1 Person, 4 x 2 Persons, 1 x 4 Persons