



PSV

Starling Tide

Vessel specs

Built / Yard	2013
Design	PSV 08 CD
Yard	STX OSV Vung Tau
Flag	REB
LOA	81,7m
Breadth Moulded	18m
Deck Dimensions	810m ² (55m x 15 - 15m)
Deck Load	2500mt
Main Class	+1A1, SF, E0, DK(+), HL(2,8), Offshore Service Vessel, Supply Vessel, LFL*, COMF-V(3), Clean Design, Oilrec, Dynpos-AUTR, FiFi I, NAUT OSV(A), Ice-C
Classification Society	DNV GL
Dynamic Positioning	DP 2 from Rolls Royce
Draft (max)	6,5m + 0m Skeg/Nozzle
Deadweight	4000mt (d=6,5m)
Deck Strength	10mt/m ²
Consumption at Service Speed	11m ³ / 24hrs @ 12,5Knots
Consumption at Economy Speed	8,5m ³ / 24hrs @ 11Knots
Base Oil	319m ³ / 2007bbbls
Brine	1270m ³ / 7988bbbls
Drill Water / WB	1915m ³ / 12045bbbls
Dry Bulk	251m ³ / 8863cuft (4 tanks)
Fuel Oil	917m ³ / 5768bbbls
Methanol	100m ³ / 629bbbls
Slop	163m ³ / 1025bbbls
Mud	1270m ³ / 7988bbbls
Pot Water	730m ³ / 4592bbbls
Accommodation	30 Persons
Cabins	12 x 1 Person, 9 x 2 Persons